

FULL HD UNDERWATER CAMERAS



Designed for installation on ROV, UUV, stationary and towed seabed video recording systems

Can operate in harsh environment for a long time
Maximum working depth is 3000 m

High image quality due to up-to-date technological innovations
Fast and efficient mounting as per individual project requirements



	Wide-angle lens camera	Zoom lens camera	High-aperture varifocal lens camera
Resolution	Full HD, 1920 x 1080	Full HD, 1920 x 1080	Full HD, 1920 x 1080
Sensor	1/2.8" 2.4 Mpx CMOS	1/2.8" 2.4 Mpx CMOS	1/2.7" 2.07 Mpx CMOS
Focal length	Fixed	Variable	Variable
Focus	Fixed	Manual	Manual
Optical sensitivity	1 lux	1 lux	0.02 lux
White balance	Auto	Auto	Auto
Protocol	RTSP	RTSP	RTSP
Video format	H.264	H.264	H.264
Web-interface	Yes	Yes	Yes
Housing material	Anodized aluminium	Anodized aluminium	Anodized aluminium
Diameter	80 mm	80 mm	108 mm
Length	117 mm	147 mm	175 mm
Weight (in air)	1.05 kg	1.20 kg	2.90 kg
Weight (in water)	0.43 kg	0.47 kg	1.30 kg
Working depth	3000 m	3000 m	3000 m
Working temperature	-10 ÷ +50 °C	-10 ÷ +50 °C	-10 ÷ +50 °C
Supply voltage	24 V DC	24 V DC	24 V DC
Connector	Subconn MCBH8M	Subconn MCBH8M	Subconn MCBH8M



Ask Subsea Ltd.
Malta, Gzira
114, The Strand, GZR1027

E-mail: ash@asksubsea.com
Web: www.asksubsea.com